

product type designation



CP 1243-7 LTE EU

Communications processor CP 1243-7 LTE EU for Connection of SIMATIC S7-1200 to LTE network in European frequency range.

transfer rate

transfer rate

- for LTE transmission
 - with downlink / maximum 42 Mbit/s
 - with uplink / maximum 5.76 Mbit/s

interfaces

- | | |
|---|-----------------------|
| number of interfaces / according to Industrial Ethernet | 0 |
| number of electrical connections | |
| • for external antenna(s) | 1 |
| • for power supply | 1 |
| number of slots | |
| • for SIM cards | 1 |
| type of electrical connection | |
| • for external antenna(s) | SMA socket (50 ohms) |
| • for power supply | 3-pole terminal block |
| slot version | |
| • for SIM card | Standard |

wireless technology

- | | |
|--|-----------------------------|
| type of mobile wireless service | |
| • is supported / SMS | Yes |
| • is supported / GPRS | Yes |
| • note | GPRS (Multislot Class 10) |
| type of wireless network / is supported | |
| • GSM | Yes |
| • UMTS | Yes |
| • LTE | Yes |
| operating frequency / for GSM transmission | 900 MHz, 1800 MHz |
| operating frequency / with UMTS transmission | 900 MHz, 2100 MHz |
| operating frequency / for LTE transmission | 800 MHz, 1800 MHz, 2600 MHz |

supply voltage, current consumption, power loss

- | | |
|--|--------|
| type of voltage / of the supply voltage | DC |
| supply voltage / external | 24 V |
| supply voltage / external / at DC / rated value | 24 V |
| relative positive tolerance / at DC / at 24 V | 20 % |
| relative negative tolerance / at DC / at 24 V | 20 % |
| consumed current | |
| • from external supply voltage / at DC / at 24 V / typical | 0.1 A |
| • from external supply voltage / at DC / at 24 V / maximum | 0.22 A |

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport 	-20 ... +60 °C -20 ... +70 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20

design, dimensions and weights

module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.133 kg
fastening method	
<ul style="list-style-type: none"> • 35 mm top hat DIN rail mounting • S7-300 rail mounting • wall mounting 	Yes No Yes

product features, product functions, product components / general

number of units	
<ul style="list-style-type: none"> • per CPU / maximum 	3

performance data

number of users/telephone numbers / definable / maximum	10
---	----

performance data / open communication

number of possible connections / for open communication	
<ul style="list-style-type: none"> • by means of T blocks / maximum 	like CPU

performance data / IT functions

number of possible connections	
<ul style="list-style-type: none"> • as email client / maximum 	1

performance data / telecontrol

suitability for use	
<ul style="list-style-type: none"> • substation 	Yes
control center connection	Telecontrol Server Basic supported
<ul style="list-style-type: none"> • by means of a permanent connection • by means of demand-oriented connection • note 	supported Connection to SCADA system using OPC interface
protocol / is supported	
<ul style="list-style-type: none"> • DNP3 • IEC 60870-5 	Yes Yes
product function / data buffering if connection is aborted	Yes; 64,000 events
number of stations / for direct communication / with Telecontrol Server Basic	
<ul style="list-style-type: none"> • in send direction / maximum • in receive direction / maximum 	3 15

performance data / teleservice

diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
product function	
<ul style="list-style-type: none"> • program download with SIMATIC STEP 7 • remote firmware update 	Yes Yes

product functions / management, configuration, engineering

configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 Basic/Professional

product functions / diagnostics

product function / web-based diagnostics	Yes
--	-----

product functions / security

firewall version	stateful inspection
product function / with VPN connection	IPsec, SINEMA RC
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56

type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1
number of possible connections / with VPN connection	1
product function	
<ul style="list-style-type: none"> password protection for teleservice access encrypted data transmission 	<p>Yes</p> <p>Yes</p>
product functions / time	
protocol / is supported	
<ul style="list-style-type: none"> NTP 	Yes
time synchronization	
<ul style="list-style-type: none"> from control center 	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

7/7/2022 